



all print supplies ltd.

Tel: 01753 696977 Fax: 01753 567733

Tel: 0844 4488686 Fax: 08700 668662

Email: sales@allprint.co.uk www.allprint.co.uk

Technical data sheet

Ruby Film for Screen Positives

PRODUCT DESCRIPTION

Soft 20 μ transparent ruby film on a 125 μ polyester film.

TYPICAL USES

For quick and easy creation of film positives. The extra thick backing makes the product very easy to cut and weed. The ruby film is opaque to any copying light.

SHELF LIFE

2 years when stored in original packaging at 21 $^{\circ}$ C and 50% RH.

PHYSICAL PROPERTIES (Average Values)

Tests made at 23 $^{\circ}$ C and 50%RH unless otherwise stated

Ruby Film Thickness - 20 microns

Liner Thickness - 125 gsm

UV light block - 100% (between 300 and 550nm UVA and UVB)

Temperature Ranges-

Application Range : plus 10 $^{\circ}$ C to plus 30 $^{\circ}$ C

Service Range: minus 5 $^{\circ}$ to plus 50 $^{\circ}$ C

APPLICATION DATA

Product can be used on most cad plotters, please ensure the cut depth is checked before starting actual job. Rolls should be stored on end, in original packaging to maintain quality.